



**Product info**

- [Add to watch list](#)
- [Request information](#)
- [Please call me back](#)
- [Similar products](#)
- [Brochures](#)
- [CAD exhibition](#)
- [Print view](#)
- [Back to overview](#)

**Home**

**News + Press**

**Products**

**Mobile car lift**

[Mobile lifts for cars](#)

[Mobile lifts for cars + vans](#)

[Ascending device for cars + vans](#)

[Ascending device for light road sweepers](#)

[Ascending device for fairway mowers](#)

[Lifts for commercial vehicles](#)

[Mobile columns for railway vehicles](#)

[Lifts for airport ground vehicles \(GSE\)](#)

[Lifts for special vehicles](#)

[Garage equipment](#)

[Product Videos](#)

**Sales + Service**

**Company**

**Imprint**

**Finkbeiner international**

[www.finkbeiner-france.fr](http://www.finkbeiner-france.fr)

[www.finkbeiner.co.uk](http://www.finkbeiner.co.uk)

**Product search**

Sprache / Language / Langue / Lengua

English

**Mobile 2-Post-Lift FHB3000-SL Standard**

for cars, SUV, vans up to medium wheel base.  
Capacity 3 t, standard drive-in width 2000 mm, asymmetric swivel arms.

**Description**

- Practical and versatile lifting solution for all types of vehicle for repair and maintenance, indoors and outdoors.
- Free access to any part of the vehicle, doors can be opened at any height.
- Maximum safety, double load securing with automatic hydraulically and mechanical locks. Automatic locking swivel arms.
- Thoroughly reliable, self-lubrication. Hydraulic drive system protected against moisture, dirt and sand. No maintenance required.



Mobile car lift also for SUV vehicles


**Detail images**



**Practice images**



**CAD exhibition**



**Specifications**

**Article no.:**

**FHB3000-02**

**Rated load capacity:**

3000 kg

**Lifting height:**

1850 mm

**Lifting time:**

40 s

Lowering time:	40 s
Synchronisation:	hydraulisch
Load supporting means:	Gelenkarme, asymmetrisch
Bottom clearance:	110 mm
Support bracket length on the front min.:	600 mm
Support bracket length on the front max.:	1070 mm
Support bracket length on the rear min.:	700 mm
Support bracket length on the rear max.:	1550 mm
Einfahrbreite:	2000 mm
Mode of drive:	elektro-hydraulisch
Motor power:	2,2 kW
Power supply:	400 VAC 3ph 50Hz
Fuse protection (electrical):	16 A
Protection class:	IP 54
Length:	2350 mm
Width:	3050 mm
Weight:	900 kg

#### Brochures



Brochure "Mobile car lift FHB3000"  
Size: 159 kB



FHB3000\_specs\_EN.pdf  
Size: 50 kB

#### Accessories



**Distance tubes LA02**  
(accessory for lift FHB3000)



**Platforms FA3-2000**  
Accessory for lift FHB3000SS/SL Standard, drive-in width 2000 mm.  
Application: inspection lift, ascending device to drive-on with vehicle, platform lift.

#### Similar products



**Mobile 2-Post-Lift FHB3000-SS Standard**  
for cars, SUV, vans with short wheel base.  
Capacity 3 t, standard drive-in width 2000 mm, symmetric swivel arms.

Article no.: FHB3000-01

>>> **FHB3000-SL Standard** Mobile 2-Post-Lift