



GARAGE EQUIPMENTS
UTENSILMACC NORD

PONTI SOLLEVATORI ELETTROMECCANICI A DUE COLONNE
ELECTROMECHANICAL 2 - POST AUTOLIFTS
PONTS ELEVEATEURS A 2 COLONNES ELECTROMECHANIQUES
ELEKTROMECHANISCHE 2-SÄULEN HEBEBÜHNEN



asimmetrico senza basamento
asymmetric without bedplate
asymétrique sans embase
asymmetrisch ohne Grundrahmen

Art. 199/D - 2,8 Ton.

Art. 199/DK - 2,8 Ton.


Art. 199/G - 3,2 Ton.

Art. 199/GK - 3,2 Ton.




Art. 199/G

Art.	199/D	199/G	199/DK	199/GK
Portata Capacity Capacité Tragfähigkeit:	2,8 Ton.	3,2 Ton.	2,8 Ton.	3,2 Ton.
Potenza motore Motor power Puissance moteur Motorleistung:	1,5+1,5 KW	2+2 KW	1,5+1,5 KW	2+2 KW
Motore trifase Three-phase motor Moteur triphasé Netzspannung:	230/400V. 50 HZ	230/400V. 50 HZ	230/400V. 50 HZ	230/400V. 50 HZ
Peso Weight Poids Gewicht:	710 Kg.	750 Kg.	720 Kg.	760 Kg.



art.199/D - 199/G



art.199/DK - 199/GK